

## Single Component Road Marking Paint



## Product Description

It is a topcoat chlorinated rubber modified, alkyd – resin based road marking paint which becomes dry very fast.

## Product Features and Advantages

It has high adhesive and impact resistance, it is flexible and can rapidly become dry. It doesn't change color over time. It makes easy the night vision due to pigment. Ready to use. It provides high adherence. Easy and fast to use. It can be applied with a roller, brush or airless spray. It has the feature to close cracks. It provides seamless monolithic application. It closes the floor as monolithic and overall. It provides water vapor permeability.

## Application and Warnings

Surfaces must be solid, dry and free from chemicals. Humidity must not exceed 5%. It must be applied 2 layers on the prepared surfaces. It must be necessarily coated with a primer for long – term. Double layer insulation paint must be applied together with a primer. Polymex single component insulation application can be implemented after the preparation of surface. It is recommended to mix the material with a mixer with low speed (300 cycle/ min) when the material stored at ambient temperature is opened until it becomes homogeneous. Then, the material is applied in a homogeneous form on the surfaces coated with airless gun or short piled roller. 0.6 kg of material is applied on each layer on average. The second layer shall be applied after 8 hours.

## Storage and Shelf Life

2 years in unopened and original packages in cold and dry places.

## Technical Specifications

Renk	Beyaz, gri veya istenilen renk
Parlaklık	Parlak veya Mat
Bağlayıcı Madde	Alkit Reçine
Parlama Noktası	-30 °C / 90
Uygulama Isısı	5-45 °C
Yoğunluk (20 °C)	1,1 gr/ml
Hacimsel Katı Madde	100%
Kuru / Yaş Film Kalınlığı	250 / 350 mikron film kalınlık
Pratik kaplama kapasitesi	3-4 m <sup>2</sup> /kg
Kuruma (25 °C)	İlk kuruma 30 – 45 dakika
Tatbik ısı limitleri	-5 °C / +45 °C
Isı Mukavemeti	90 °C
UV	Dayanıklıdır.
Tatbik şekli	Fırça, Rulo, Çelik mala, Airless
Karışım ömrü	Yaklaşık 5 saat
Karışım Oranı	Tek Bileşenli

## Areas of Application

In old and new terraces, roof gutters, balcony wet volumes, basement walls, water reservoirs etc. places, swimming pool insulation and large glass dilations, ceramic top and ceramic bottom insulations.

## Attention

Store in well ventilated closed places, wear masks and gloves, don't touch directly and inhale the vapor, keep away from open ignition sources.

