Bitumen Based Primer





Product Description

P – 884 – is bitumen based, single component, liquid, emulsion coating, waterproof primer material. Polymex Bitumen Primer is a bitumen based water insulation material designed to be used as a primer for single component, bitum based liquid, especially, bitumen based water insulation materials or bitumen based water insulation membranes.

Surface Preparation

P- 884 – Bitumen based Primer Application surface must be cleaned of dirt, dust, plaster and cement residues, disintegrants such as paint and grease and must be free from damaged and loose parts.

In case of necessity for surface repair, surface correction and repair process must be implemented at least one day before the application of Polymex Bitumen Primer using surface repair materials $P-999-or\ P-996$. Before the application of mineral and absorbent surfaces, Polymex Bitumen Primer must be thinned in proportion as 25%. P-884-Bitumen based Primer

Areas of Application

- Water insulation of underground structures
- Water insulation of fundaments and terraces
- Insulation of humid rooms
- Insulated roofs and verandas.

Consumption

P - 884 - Bitumen based Primer: 0,400 kg/ m (may vary depending on the suction of surface).

Application

Polymex Bitumen Primer must be applied at least two coats on the properly prepared surface with a brush, roller or by spraying. The second coat application must be made after the first coat is completely dry. The second coat application must be made perpendicular to the direction of the first coat.

Storage

It must be stored between +5 °C - + 35 °C. It must be stored in a closed place being protected from sunlight and extreme temperatures. It must be stored in the air-conditioned sections under hot climatic conditions. The product must be stored at temperature above 10 °C under cold climatic conditions. It must not be frozen. In case of compliance with the above mentioned storage conditions, its shelf life in unopened package is 12 months.

Safety Rules

Gloves must be worn during the application of P - 884 – Bitumen based Primer. Skin and eye contact with product must be avoided. The contact area should be washed with plenty of water in case of contact with product. You should consult a doctor immediately if swallowed.



